

Universal Profiles – Universally Popular

These multi purpose standard size profiles are used for numerous architectural and other applications.

- Mill from stock – Immediate availability
- Anodised stock (S) – Superb matt finished effect
- 4 metre lengths – Easy lightweight handling
- Grade 6063T5 – Suitable for anodising

* (S)

Items shown with (S) suffix are also available from stock in Anodised finish. Please use this code ref if this finish is required eg GA 0319 (S) Specification 6063T5

If mill is required please order without specifying the (S) suffix.


new

Order on-line at www.goodingalum.com

Call the GA Helpline and discuss your requirements with one of our knowledgeable Project Managers
Monday-Friday 8.30am-5.00pm


020 8692 2255

Flat Bar




Flat Bar	a	b	length
Order code	mm	mm	m
GA 0101 (S)	9.5	3.2	4
GA 0103 (S)	12.7	3.2	4
GA 0108 (S)	15.8	3.2	4
GA 0114 (S)	19.0	3.2	4
GA 0124 (S)	25.4	3.2	4
GA 0132 (S)	31.7	3.2	4
GA 0141 (S)	38.1	3.2	4
GA 0157 (S)	50.8	3.2	4
GA 0191 (S)	76.2	3.2	4
GA 0178 (S)	101.6	3.2	4

Equal Angle




Equal Angle	a	b	c	length
Order code	mm	mm	mm	m
GA 0300	9.5	9.5	1.6	4
GA 0301 (S)	12.7	12.7	1.6	4
GA 0302 (S)	12.7	12.7	3.2	4
GA 0304 (S)	15.8	15.8	1.6	4
GA 0305 (S)	15.8	15.8	3.2	4
GA 0310 (S)	19.0	19.0	1.6	4
GA 0311 (S)	19.0	19.0	3.2	4
GA 0312 (S)	22.2	22.2	3.2	4
GA 0318 (S)	25.4	25.4	1.6	4
GA 0319 (S)	25.4	25.4	3.2	4
GA 0326 (S)	31.7	31.7	1.6	4
GA 0327 (S)	31.7	31.7	3.2	4
GA 0334 (S)	38.1	38.1	1.6	4
GA 0335 (S)	38.1	38.1	3.2	4
GA 0339 (S)	44.4	44.4	3.2	4
GA 0365 (S)	50.8	50.8	1.6	4
GA 0346 (S)	50.8	50.8	3.2	4
GA 0355 (S)	76.2	76.2	3.2	4

Unequal Angle




Unequal Angle	a	b	c	length
Order code	mm	mm	mm	m
GA 0303 (S)	15.8	9.5	1.6	4
GA 0306 (S)	19.0	6.5	1.6	4
GA 0307 (S)	19.0	9.5	1.6	4
GA 0308c	19.0	12.7	1.6	4
GA 0309 (S)	19.0	12.7	3.2	4
GA 0313 (S)	25.4	12.7	1.6	4
GA 0314 (S)	25.4	12.7	3.2	4
GA 0316 (S)	25.4	19.0	1.6	4
GA 0317 (S)	25.4	19.0	3.2	4
GA 0324 (S)	31.7	19.0	3.2	4
GA 0325 (S)	31.7	25.4	3.2	4
GA 0331 (S)	38.1	12.7	3.2	4
GA 0332 (S)	38.1	19.0	3.2	4
GA 0333 (S)	38.1	25.4	3.2	4
GA 0338 (S)	44.4	22.2	3.2	4
GA 0366 (S)	50.8	12.7	3.2	4
GA 0340 (S)	50.8	19.0	3.2	4
GA 0341 (S)	50.8	25.4	3.2	4
GA 0344 (S)	50.8	38.1	3.2	4
GA 0351 (S)	76.2	25.4	3.2	4
GA 0353 (S)	76.2	50.8	3.2	4

Tee



Tee	a	b	c	length
Order code	mm	mm	mm	m
GA 0500 (S)	12.7	12.7	1.6	4
GA 0502 (S)	19.0	19.0	3.2	4
GA 0514 (S)	25.4	25.4	1.6	4
GA 0504 (S)	25.4	25.4	3.2	4
GA 0506 (S)	31.7	31.7	3.2	4
GA 0507 (S)	38.1	38.1	3.2	4
GA 0510 (S)	50.8	50.8	3.2	4

Channel



+ Allow for a minus tolerance on this dimension

Channel	a	b	c	d	e+	length
Order code	mm	mm	mm	mm	mm	m
GA 0400 (S)	12.7	12.7	12.7	1.6	9.3	4
GA 0401 (S)	12.7	12.7	12.7	3.2	6.3	4
GA 0402 (S)	15.8	15.8	15.8	1.6	12.7	4
GA 0403 (S)	15.8	15.8	15.8	3.2	9.3	4
GA 0404 (S)	19.0	12.7	12.7	3.2	12.7	4
GA 0405 (S)	19.0	19.0	19.0	3.2	12.7	4
GA 0406 (S)	22.2	22.2	22.2	3.2	15.8	4
GA 0407 (S)	25.4	12.7	12.7	3.2	19.0	4
GA 0408 (S)	25.4	19.0	19.0	3.2	19.0	4
GA 0409 (S)	25.4	25.4	25.4	3.2	19.0	4

Channel	a	b	c	d	e+	length
Order code	mm	mm	mm	mm	mm	m
GA 0441	25.4	38.1	38.1	3.2	19.0	4
GA 0414	31.7	19.0	19.0	3.2	25.4	4
GA 0419	38.1	25.4	25.4	3.2	31.7	4
GA 0423	50.8	25.4	25.4	3.2	44.4	4
GA 0430	76.2	25.4	25.4	3.2	69.8	4
GA 0432	76.2	50.8	50.8	3.2	69.8	4