

Fixing Instructions

GA Column Casing Type CC2 with GA Ver T Fix

These instructions tell you about installing GA Column Casing Type CC2 with GA Ver T Fix. Please read these instructions before using this product. If there is anything you do not understand or if you want to know more about this item, please contact GA.

GA column casings must be installed by suitably qualified contractors with the required knowledge and expertise. Current standard construction methods must be used.

The contractor has the responsibility and duty to ensure proper safety so that during and after completion of the installation the column casing remains firmly fixed in situ.

Before beginning installation also refer to [GA Sitework Data Sheet](#) for guidance on Off-loading, Site Storage and Installation.

Step 1: Carefully unpack the column casing panels and Ver T Fix panel hanging strips.

Step 2: Inspect the support nibs on the Ver T Fix panel hanging strips to ensure these are undamaged.

Step 3: Secure the Ver T Fix fixing strips to the fixing surface by using suitable screws/fixings (No. 6 size supplied by others). It is important that fixings are secured through all of the pre-punched holes.

Step 4: Offer the column casing panel up to the Ver T Fix hanging strips and locate securely into position.

NB GA Column Casings supplied by Gooding Aluminium are not intended to have electrical wiring installed. Where this is a requirement the specifier and installer should ensure that all Regulations have been complied with and in particular that consideration has been given to the CENELEC HD 384 series of documents. (CENELEC HD 384 Series: Electrical Safety in Buildings (20 Parts))

Issue 1:5/08

