



GA Profiles Tee, Channel



+ Allow for a minus tolerance on this dimension

Order code	a mm	b mm	c mm	length m
GA 0500	12.7	12.7	1.6	4
GA 0502 (S)	19.0	19.0	3.2	4
GA 0514 (S)	25.4	25.4	1.6	4
GA 0504 (S)	25.4	25.4	3.2	4
GA 0506 (S)	31.7	31.7	3.2	4
GA 0507 (S)	38.1	38.1	3.2	4
GA 0509	50.8	25.4	3.2	4
GA 0510 (S)	50.8	50.8	3.2	4

Order code	a mm	b mm	c mm	d mm	e+ mm	length m
GA 0400 (S)	12.7	12.7	12.7	1.6	9.3	4
GA 0401 (S)	12.7	12.7	12.7	3.2	6.3	4
GA 0402 (S)	15.8	15.8	15.8	1.6	12.7	4
GA 0403 (S)	15.8	15.8	15.8	3.2	9.3	4
GA 0404 (S)	19.0	12.7	12.7	3.2	12.7	4
GA 0405 (S)	19.0	19.0	19.0	3.2	12.7	4
GA 0406 (S)	22.2	22.2	22.2	3.2	15.8	4
GA 0407 (S)	25.4	12.7	12.7	3.2	19.0	4
GA 0408 (S)	25.4	19.0	19.0	3.2	19.0	4
GA 0409 (S)	25.4	25.4	25.4	3.2	19.0	4
GA 0441	25.4	38.1	38.1	3.2	19.0	4
GA 0413	31.7	12.7	12.7	3.2	25.4	4
GA 0414	31.7	19.0	19.0	3.2	25.4	4
GA 0415	31.7	25.4	25.4	3.2	25.4	4
GA 0416	31.7	31.7	31.7	3.2	25.4	4
GA 0418	38.1	19.0	19.0	3.2	31.7	4
GA 0419	38.1	25.4	25.4	3.2	31.7	4
GA 0423	50.8	25.4	25.4	3.2	44.4	4
GA 0430	76.2	25.4	25.4	3.2	69.8	4
GA 0432	76.2	50.8	50.8	3.2	69.8	4

Specification 6063 T5
 Items listed available from stock in mill finish
 When specifying please quote the GA order code
 Items shown with (S) suffix are available from stock in Ano-Sil anodised finish. Please quote this code ref if this finish is required eg GA 0124 (S).

GA Helpline 020 8692 2255 Mon-Fri 8.30am-5pm for professional assistance
www.goodingalum.com sales@goodingalum.com

© 2007 Gooding Aluminium Limited

